



DOOR WARMER

Bundy Refrigeration supplies custom designed steel door warmers that provide an energy-efficient and cost effective solution for condensate elimination around door openings on freezers and fridge-freezers.

Door warmers can be supplied in electricwelded single wall tubing, according to customer requirements. A variety of coatings are available to meet various corrosion resistance needs.

CHARACTERISTICS

Raw Material

Tubing	Electricwelded steel tube as per SAE J526 - Jan/2000
	Standard: Ø4,00; 4,20; 4,76 WT 0,50; 0,71
Coating	Standard Hot Dipped Galvanized (HDG) Corrosion resistance: 48-72 hrs depending on thickness* Also available: Plain or Copper coated Aluminized: up to 3000 hrs <small>*Hours before formation of red rust according to ASTM B117 salt spray resistance test.</small>

We are the name behind the world's leading refrigeration appliances

Bundy delivers safe, high-quality, technology-driven heat transfer and fluid-carrying components to meet the demands of global brands in the refrigeration and household appliance industry.

Every day, Bundy know-how puts more than 60 years of experience to work. With facilities throughout Europe and the Americas, Bundy serves the needs of an industry the world relies on.



BUNDY
REFRIGERATION

Head Office Contact
BUNDY REFRIGERATION
Centrum House
38 Queen Street Glasgow
Scotland G1 3DX

For info and inquiries:
T: +39 0143 638670

e: info@bundyrefrigeration.com
w: www.bundyrefrigeration.com